

## MS 280 C-BQ Chain Saw

Mid-Range Use



16 in. Bar : **\$549.95**

18 in. Bar : **\$559.95**

20 in. Bar : **\$569.95**

### Distributor Suggested Retail Price

All pricing on this site is Distributor Suggested Retail Price. This site strives to maintain accurate and current suggested retail pricing. However, dealers' actual prices may vary or change. Please confirm pricing with your dealer.

### Series 1133

#### Mid-Range Use

If you thought the MS 280 couldn't get any better, guess again. Equipped with our Intelligent Engine Management system, this chain saw also has the additional convenience of a second chain braking system that stops the chain in less than a second when the rear handle is completely released—a STIHL exclusive you won't find anywhere else. A combination of features others simply can't match.

#### Standard Features

- Advanced anti-vibration system
- Heavy-duty air filter for longer cleaning intervals
- Toolless fuel and oil caps with retainers
- Carburetor preheat shutter for summer/winter operation
- Intelligent Engine Management (**IEM**) technology
- STIHL Quickstop and a second chain braking system (**Q**) Exclusive to STIHL
- Exclusive toolless Quick Chain Adjuster (**QCA**) for fast and easy chain adjustment (**B**)
- ElastoStart™ starter handle

#### Specifications

DISPLACEMENT	54.7 cc (3.33 cu. in.)
ENGINE POWER	2.7 kW (3.6 bhp)
WEIGHT (powerhead only)	5.5 kg (12.1 lbs.)
FUEL CAPACITY	520 cc (17.6 oz.)
CHAIN OIL CAPACITY	280 cc (9.5 oz.)
OILOMATIC® CHAIN	.325" RMC3
RECOMMENDED RANGE OF GUIDE BAR LENGTHS	40 to 50 cm (16" to 20") STIHL ROLLOMATIC® E

STIHL recommends #3634 (26 RMC3 67) OILOMATIC® saw chain and 16" 3003 008 6813 Ematic™ guide bar combination.

#### IMPORTANT INFORMATION

**WARNING!** The occurrence called "kickback" can cause serious or fatal injury. Always read the instruction manual carefully before using your saw. STIHL uses a green and yellow color-coding system to help you select a powerhead, bar and chain combination that complies with the kickback requirements of ANSI Standard B175.1 (gasoline-powered saws) and §30 of UL 1662/ ANSI Standard B175.1 (electric chain saws). Ask your STIHL dealer about safe operating procedures and the advantages of the STIHL Quickstop® chain brake, STIHL second chain braking system (Q), STIHL reduced kickback bars and STIHL low-kickback saw chains.

STIHL recommends the use of green reduced kickback bars and green low kickback chains on all STIHL chain saws.

**WARNING!** Improper use of any power tool may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your instruction manual before using such products.

**STIHL products sold through U.S. STIHL dealers are for distribution in the United States only.**