

**Oilomatic® Saw Chains**

No Classification



**IMPORTANT INFORMATION**

**WARNING!** The occurrence called "kickback" can cause serious or fatal injury. Always read the instruction manual carefully before using your saw. STIHL uses a green and yellow color-coding system to help you select a powerhead, bar and chain combination that complies with the kickback requirements of ANSI Standard B175.1 (gasoline-powered saws) and §30 of UL 1662/ ANSI Standard B175.1 (electric chain saws). Ask your STIHL dealer about safe operating procedures and the advantages of the STIHL Quickstop® chain brake, STIHL second chain braking system (Q), STIHL reduced kickback bars and STIHL low-kickback saw chains. STIHL recommends the use of green reduced kickback bars and green low kickback chains on all STIHL chain saws.

**WARNING!** Improper use of any power tool may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your instruction manual before using such products.

STIHL products sold through U.S. STIHL dealers are for distribution in the United States only.

**OILOMATIC® STIHL PICCO™ Micro™ Narrow (PMN)**



PMN OILOMATIC® STIHL PICCO™ Micro™ Narrow saw chain. Developed to increase cutting efficiency over PM or PM1 chain. Meets ANSI requirements for low kickback chain. Cutting efficiency is 13% greater than PM1. Weight is reduced by 30% over PM chain. Kerf is narrower than PM or PM1.



● Low kickback chain.

**0.043"**  
**1/4" .325" 3/8" .404" PICCO**  
**3/8"**  
**3982**

**OILOMATIC® STIHL PICCO™ Micro™ (PM)**



This saw chain was specially developed for the smaller STIHL saws. The major advantage of the OILOMATIC® STIHL PICCO™ chain is its high degree of smoothness during operation. Although the STIHL PICCO™ Micro™ has a pitch of 3/8", the special shape of all component parts gives the OILOMATIC® STIHL PICCO™ a different profile from other 3/8" pitch chains and is designed for use on smaller, less powerful chain saws.



◆ **WARNING!**

**0.050"**  
**1/4" .325" 3/8" .404" PICCO**  
**3/8"**  
**3997**